PT9RUE

TOUCH SCREEN LCD DISPLAY

Panel Type	19.0” TFT Active Matrix Panel
Max. Resolution	1280 × 1024 SXGA@75Hz
Pixel Pitch	0.294 (H) × 0.294 (V)
Contrast Ratio	1,000:1
Brightness	250 cd/m2
Display Area	376 ×301 mm
Response Time	5ms (Typ.)
Display Colors	16.7M
Viewing Angle	170°(H)/160°(V)
Signal Connector	VGA
VGA Input Signal	RGB Analog 0.7V Peak to Peak
OSD Control	Power Switch, Menu, Select (+, -), Auto
Operation Temperature	0° ~ 50° C
Storage Temperature	-20° ~ 60° C
Power Consumption	40 W
Power Supply	External Power Adapter
Safely & EMI	CE, FCC, TUV-GS, UL Compliant
Touch screen	Resistive; USB
Demension	445 x 388 x 85mm 17.5” x 15.27” x 3.34”
Weight	15lbs (6.80 kg)

ACCUVIEW INC•
Tel: 800.275.4255 Fax: 201.440.5655 Address: 40C Cotters Lane, Suite F, East Brunswick NJ 08816 Email: sales@accuview.com
*Specifications subject to change without notice. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2008 Accuview Inc. All rights reserved.